



## PTO SHAFTS




Continuous operation data and conditions, working angle 5°, average life 1000 hours.


Profile	Type	540 r.p.m.				1000 r.p.m.				max dynamic torque		standard	CvJ single joint	CvJ double joint
		kW	CV	Nm	in.lb.	kW	CV	Nm	in.lb.	Nm	in.lb.			
<b>V</b> 	<b>20</b>	17	23	300	2650	26	36	250	2200	460	4050	●	●	●
	<b>40</b>	28	38	490	4310	43	58	410	3600	850	7530	●	●	●
	<b>50</b>	37	50	650	5750	57	77	540	4750	1100	9740	●		
	<b>60</b>	50	68	880	7790	77	105	740	6510	1510	13360	●	●	●
	<b>80</b>	74	100	1300	11500	113	154	1080	9550	2390	21150	●	●	●
	<b>90</b>	88	120	1560	13800	140	190	1340	11850	2900	25700	●		

Profile	Type	540 r.p.m.				1000 r.p.m.				max dynamic torque		standard	CvJ single joint	CvJ double joint
		kW	CV	Nm	in.lb.	kW	CV	Nm	in.lb.	Nm	in.lb.			
<b>T</b> 	<b>10</b>	12	16	210	1850	18	25	172	1500	320	2850	●		
	<b>20</b>	15	21	270	2400	23	31	220	1950	450	4000	●	●	●
	<b>40</b>	26	35	460	4050	40	55	380	3350	780	6900	●	●	●
	<b>50</b>	35	47	620	5500	54	74	520	4600	1050	9300	●		
	<b>60</b>	47	64	830	7350	74	100	710	6259	1450	12850	●	●	●
	<b>80</b>	70	95	1240	10950	110	150	1050	9300	2250	19900	●	●	●
	<b>90*</b>	88	120	1560	13800	140	190	1340	11850	2900	25700	●		

\* Spare parts only available

Profile	Type	540 r.p.m.				1000 r.p.m.				max dynamic torque		standard	CvJ single joint	CvJ double joint
		kW	CV	Nm	in.lb.	kW	CV	Nm	in.lb.	Nm	in.lb.			
<b>E</b> 	<b>40*</b>	26	35	460	4050	40	55	380	3350	780	6900	●	●	●
	<b>50*</b>	35	47	620	5500	54	74	520	4600	1050	9300	●		
	<b>60*</b>	47	64	830	7350	74	100	710	6259	1450	12850	●	●	●
	<b>80*</b>	70	95	1240	10950	110	150	1050	9300	2250	19900	●	●	●
	<b>90*</b>	88	120	1560	13800	140	190	1340	11850	2900	25700	●		

\* Spare parts only available

Profile	Type	540 r.p.m.				1000 r.p.m.				max dynamic torque		std.	CvJ single joint	CvJ double joint
		kW	CV	Nm	in.lb.	kW	CV	Nm	in.lb.	Nm	in.lb.			
<b>D</b> 	<b>120</b>	144	196	2546	22535	221	300	2110	18675	6500	57530	●		

